

4Ch Stand Alone DVR

LDV-S802 (4 channel)



Feature

- Triplex (Live display, Recording, Network)
- RTOS Operating System
- Small File Sizes by MPEG-4 Compression
- Various Recording resolution (720x480, 720x240, 360x240)
- Up to 120FPS@360 X 240 Recording
- Up to 500GB Internal Storage (Expandable if new high capacity HDD is launched)
- Various Monitor Output (Video out, Loop, VGA, S-VHS, Spot)
- 4 Audio input Channels
- Support PS2 Mouse, IR Remote Controller
- One USB 2.0 Port (Front)
- Various Search Function (Date/Time Search, Event Search, Go to First, Go to Last)
- Multi-Site Web Viewer
- Multi-Site PC Client Software
- Multi-Languages Selectable
- Alarm Notification by e-Mail
- Pre-Alarm Recording
- Easy System S/W Update with USB Memory Stick
- Image Rate & Quality Adjustment per Individual Camera
- Daylight Saving Mode

Specifications

Model		LDV-S802	
Video	Input		4
	Output	Loop Through	4
		Composite	1
		S-Video	1
		VGA	1
	Spot	1	
Audio	Input		4
	Output		1
Alarm	Input		4
	Output		1
	Pre-Alarm Recording		Yes
Recording	Image Rate (/Sec)	NTSC	Up to 120 FPS @ 360x240
			Up to 60 FPS @ 720x240
			Up to 30 FPS @ 720x480
		PAL	Up to 100 FPS @ 360x288
			Up to 50 FPS @ 720x288
			Up to 25 FPS @ 720x576
Search	Playback Function		FF, FB, Frame Advance, 5Mins Skip
	Search Mode		Date/time, Event (Motion, Alarm), Go to First, Go to Last
Display	Image Rate (/Sec)	NTSC	120 FPS (Real time per each channel)
		PAL	100 FPS (Real time per each channel)
	Division Mode		1, 4, PIP (Quad-1,2,3, 3Way-1,2,3,2Way-1)
Internal HDD	Max Capacity		500GB (Up to 2 HDDs)
Backup	Backup Interface		USB 2.0 X 1 Network
	Supportable Devices		Memory Stick
PTZ	PTZ Control Interface		RS-485 x1
Network	Network Connection		Ethernet 10/100M (RJ-45)
	Network Transmission Speed		120fps (CIF)
Security	Password Protection		Yes
Power			DC 12V 5A 50/60Hz, ADAPTER
Dimension (WxDxH mm)			430x315.5x54
Operation Temp. / Humidity			0 °C ~ 40 °C / 0%RH ~ 80%RH

Rear View



Dimension (unit : mm)

